



# 30ACi+ Connect

### Battery Backup System

- Fully automatic auxiliary power source
- Backup system runs on AC or DC power
- Runs the same 1/8 HP pump in AC or DC mode
- Ion+

  © Connect digital level control sensor with integrated alarms
- The lon+ Connect comes with a cellular plan, so there is no need to call a provider for set up. Simply call lon Technologies (815-886-9200) to turn on your lon+ Connect.





## 30ACi+ Connect


Battery Backup System

#### Typical Installation Diagram




- 1. Ion+ Connect
- 2. Battery box with inverter
- 3. Ion<sub>®</sub> StormPro<sub>®</sub> sump pump
- 4. Ion+Connect digital level control/alarm sensor
- 5. Recommended minimum basin size: 18" x 24" (not included)

#### System Performance



#### Pump Performance



#### System Specifications

- ½ HP pump with PSC, energy efficient motor: 4.0 amps
- Up to 45 GPM
- Fully automatic, converts 12 volt DC to 120 volt AC when utility power is lost
- Runs 1/3 HP pump on AC or DC power
- Inverter has digital display, tells status of system at all times
- Requires one 12 volt deep cycle AGM battery (battery is NOT included)
- Non-corrosive battery enclosure
- Includes piggyback Ion+ Connect digital level control/alarm sensor with no moving parts
- Built-in alarm and monitoring system with Power, System and High Water LEDs and audible alarm
- Dry contacts to connect to a monitoring device via an RJ11 connection
- Rated at 2 million cycles, it will last 4 times longer than a standard pump switch
- Quick and easy installation
- 3 year warranty